

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Starbond EMP-1500 Pink Thick

#### 1.2. Intended Use of the Product

**Use of the Substance/Mixture:** For industrial or professional use only.

#### 1.3. Name, Address, and Telephone of the Responsible Party

##### Company

CPH International  
 611 S. Catalina St.  
 Suite 400 A/B  
 Los Angeles, CA 90005  
 T: 213-382-7788

[www.starbond.com](http://www.starbond.com)

##### Manufacturer

Starbond  
 611 S. Catalina St.  
 Suite 400 A/B  
 Los Angeles, CA 90005  
 T: 213-382-7788

#### 1.4. Emergency Telephone Number

**Emergency Number** : 1-800-900-4583 (GLUE)

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

##### GHS-US Classification

Acute Tox. 4 (Inhalation:dust,mist)	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Carc. 2	H351
STOT SE 3	H335

Full text of hazard classes and H-statements : see Section 16.

#### 2.2. Label Elements

##### GHS-US Labeling

**Hazard Pictograms (GHS-US)** :



**Signal Word (GHS-US)** :

Warning

**Hazard Statements (GHS-US)** :

H315 - Causes skin irritation.  
 H317 - May cause an allergic skin reaction.  
 H319 - Causes serious eye irritation.  
 H332 - Harmful if inhaled.  
 H335 - May cause respiratory irritation.  
 H351 - Suspected of causing cancer.

**Precautionary Statements (GHS-US)** :

P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P261 - Avoid breathing vapors, mist, or spray.  
 P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
 P271 - Use only outdoors or in a well-ventilated area.  
 P272 - Contaminated work clothing must not be allowed out of the workplace.  
 P273 - Avoid release to the environment.  
 P280 - Wear protective gloves, protective clothing, and eye protection.  
 P302+P352 - If on skin: Wash with plenty of water.  
 P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308+P313 - If exposed or concerned: Get medical advice/attention.

# Starbond EMP-1500 Pink Thick

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P312 - Call a poison center or doctor if you feel unwell.  
P321 - Specific treatment (see Section 4 on this SDS).  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixture

Name	Product Identifier	%
Ethyl cyanoacrylate	(CAS-No.) 7085-85-0	> 99
Poly Methyl Methacrylate	(CAS-No.) 9011-14-7	
Hydroquinone	(CAS-No.) 123-31-9	< 0.2

Full text of H-phrases: see Section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First-aid Measures

**First-aid Measures General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**First-aid Measures After Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention.

**First-aid Measures After Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

**First-aid Measures After Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**First-aid Measures After Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**Symptoms/Injuries:** Causes serious eye irritation. Causes skin irritation. May cause respiratory irritation. Harmful if inhaled. Skin sensitization. Suspected of causing cancer.

**Symptoms/Injuries After Inhalation:** Irritation of the respiratory tract and the other mucous membranes. Inhalation is likely to cause adverse health effects including but not limited to: irritation, difficulty breathing, and unconsciousness.

**Symptoms/Injuries After Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

**Symptoms/Injuries After Eye Contact:** Contact causes severe irritation with redness and swelling of the conjunctiva.

**Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** Suspected of causing cancer.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Carbon dioxide, dry chemical.

**Unsuitable Extinguishing Media:** Application of water to product may generate heat and increase fire intensity.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

# Starbond EMP-1500 Pink Thick

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Oxides of carbon, oxides of nitrogen, irritating organic vapors.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions. Ventilate area.

**Methods for Cleaning Up:** Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Rapid exothermic polymerization occurs in the presence of water, amines, alkalis and alcohols.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with eyes, skin and clothing. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

**Incompatible Materials:** Water, alcohol, amines, and alkalis.

### 7.3. Specific End Use(s)

For industrial or professional use only.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in Section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Ethyl cyanoacrylate (7085-85-0)		
USA ACGIH	ACGIH TWA (ppm)	0.2 ppm
Hydroquinone (123-31-9)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
USA ACGIH	ACGIH chemical category	dermal sensitizer, Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
USA IDLH	US IDLH (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>

# Starbond EMP-1500 Pink Thick

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


## 8.2. Exposure Controls

### Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when toxic gases may be released.

### Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



### Materials for Protective Clothing

: Chemically resistant materials and fabrics.

### Hand Protection

: Wear protective gloves.

### Eye and Face Protection

: Chemical safety goggles.

### Skin and Body Protection

: Wear suitable protective clothing.

### Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

### Other Information

: When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Pink Clear Liquid
Odor	: Pungent Odor
Odor Threshold	: 1-2 ppm
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: < -30 °C (< -22 °F)
Boiling Point	: 54 - 56 °C (129.2 - 132.8 °F)
Flash Point	: > 84 °C (> 183.2 °F) [Test Method: Closed Cup]
Auto-ignition Temperature	: 485 °C (905 °F)
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor Pressure	: < 0.27 kPa @ 25 °C (77 °F)
Relative Vapor Density at 20°C	: 4.3
Relative Density	: No data available
Density	: 1 - 1.1 g/ml
Solubility	: Insoluble in Water; Soluble in Acetone
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: 1300-1700 mPa.s @ 20 °C (68 °F)
Lower Flammable Limit	: 1.7 %

### 9.2. Other Information

No additional information available

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see Section 7).
- 10.3. Possibility of Hazardous Reactions:** Material polymerizes rapidly with contact with water, alcohol, amines, and alkalis.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. Incompatible Materials:** Water, alcohol, amines, and alkalis.
- 10.6. Hazardous Decomposition Products:** None expected under normal conditions of use.

# Starbond EMP-1500 Pink Thick

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects

**Acute Toxicity:** Inhalation:dust,mist: Harmful if inhaled.

Starbond EMP-1500 Pink Thick	
ATE (Dust/Mist)	1.52 mg/l/4h
Ethyl cyanoacrylate (7085-85-0)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	< 5.275 mg/l/4h U.S. Environmental Protection Agency December, 2014-converted to 4-hour exposure from 1 hour exposure.
ATE (Dust/Mist)	1.50 mg/l/4h
Hydroquinone (123-31-9)	
LD50 Oral Rat	298 mg/kg
LD50 Dermal Rabbit	74800 mg/kg

**Skin Corrosion/Irritation:** Causes skin irritation.

**Serious Eye Damage/Irritation:** Causes serious eye irritation.

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Suspected of causing cancer.

Hydroquinone (123-31-9)	
IARC group	3
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity.

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** May cause respiratory irritation.

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** Irritation of the respiratory tract and the other mucous membranes. Inhalation is likely to cause adverse health effects including but not limited to: irritation, difficulty breathing, and unconsciousness.

**Symptoms/Injuries After Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

**Symptoms/Injuries After Eye Contact:** Contact causes severe irritation with redness and swelling of the conjunctiva.

**Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** Suspected of causing cancer.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Hydroquinone (123-31-9)	
LC50 Fish 1	0.044 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 Daphnia 1	0.29 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	0.044 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
NOEC Chronic Crustacea	0.003 mg/l
NOEC Chronic Algae	0.0015 mg/l

### 12.2. Persistence and Degradability

Starbond EMP-1500 Pink Thick	
Persistence and Degradability	Not established.

### 12.3. Bioaccumulative Potential

Starbond EMP-1500 Pink Thick	
Bioaccumulative Potential	Not established.
Hydroquinone (123-31-9)	
BCF Fish 1	40
Log Pow	0.5

# Starbond EMP-1500 Pink Thick

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 12.4. Mobility in Soil

No additional information available

## 12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste Treatment Methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations.

**Additional Information:** Container may remain hazardous when empty. Continue to observe all precautions.

**Ecology - Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### 14.1. In Accordance with DOT

**Proper Shipping Name** : COMBUSTIBLE LIQUID, N.O.S. (Ethyl cyanoacrylate )  
**Identification Number** : NA1993  
**Packing Group** : III  
**ERG Number** : 128

### 14.2. In Accordance with IMDG

Not regulated for transport

### 14.3. In Accordance with IATA

**Proper Shipping Name** : AVIATION REGULATED LIQUID, N.O.S., (Ethyl cyanoacrylate )  
**Packing Group** : III  
**Identification Number** : UN3334  
**Hazard Class** : 9  
**Label Codes** : 9  
**ERG Code (IATA)** : 9A



## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

<b>Starbond EMP-1500 Pink Thick</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Immediate (acute) health hazard Delayed (chronic) health hazard
<b>Ethyl cyanoacrylate (7085-85-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Hydroquinone (123-31-9)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302 Subject to reporting requirements of United States SARA Section 313	
<b>CERCLA RQ</b>	100 lb
<b>SARA Section 302 Threshold Planning Quantity (TPQ)</b>	500 - 10000 lb
<b>SARA Section 313 - Emission Reporting</b>	1 %

### 15.2. US State Regulations

<b>Ethyl cyanoacrylate (7085-85-0)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List
<b>Hydroquinone (123-31-9)</b>
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest Revision** : 12/12/2017

# Starbond EMP-1500 Pink Thick

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

### GHS Full Text Phrases:

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Carc. 2	Carcinogenicity Category 2
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

SDS US (GHS HazCom)